Blue Nile Region

Water, Environmental and Sanitation Project (WES)



GEOPHYSICAL STUDY FOR LOCATED SITE FOR MINI WATER YARD AT MEDIUM

MEDIUM VILLAGE

BAU – LOCALITY

PREPARED BY: HYDRO GEOPHYSICIST: SALAH ELDOMA ABD ALLA ABD ALRAHMAN

WES Project Blue Nile

23/April /2026

Abdelrhman M.Ahmed For Contractings

-

Geophysical study to locate suitable site for Groundwater borehole drilling (Mini Water Yard) in Medium Area –Bau Locality – Blue Nile Region .

1- Study area

The study area lies in Medium Village which located about 40 KM South east Damazin town (the capital of Blue Nile Region)

2- Objectives and methodology

The main objectives of this study are to locate sitable site for drilling of water borehole for Mini water yard.

These objectives will be achieved through the following methodological steps:

- Assessment of the groundwater conditions in the study area.
- Conduction Geophysical study using electrical resistivity methods (Vertical Electrical Sounding VES) at selected site to detect potential water-bearing horizons.
- Collection and analysis of existing well data to support the study.
- Integration of all results to provide recommendations for selecting the most suitable location for water well drilling.



- Geology and Geomorphology of the study area :

The general geology of the Blue Nile Region consists of the following geologic units

- The basement complex Rocks
- Alatshan formation
- Alluvian Deposits
- Superficial Deposits

The superficial deposits are Pleistocene to recent unconsolidated sediments which are mainly composed of clays, sands and gravels that are distributed over most of the region. It forms the dark grey thick soil (cotton soil) which is very good for agriculture. In addition to very weathered basement cropped out around and loose sand that is confined to the beds of the wadis and its tributaries. Wadi Medium which runs west east ward represents the main drainage in the area, consists of sand and clay are deposited. The basement complex rocks are of Precambrian age and cover all the study area. It composed of metamorphic and igneous rocks including gneiss, schists, followed by Paleozoic granite and quartzites. All these units are cropping out in different parts of the area Medium , Kilgo and Abugarin mountains and vicinity. The crystalline rocks are also expected to provide aquifers in their weathered and/or fractured parts in case of good recharge conditions.



Location Map





Geophysical work:

The geophysical work conducted in the study area consisted mainly of electrical resistivity measurements. It consists of two methods: Horizontal Electrical Resistivity Profiling (HEP) and Vertical Electrical Sounding (VES), performed using a geophysical SARIS apparatus. This method was used to investigate the subsurface geological and hydrogeological conditions of the study sites.
The objectives of the geophysical survey were to :
a. Determine the vertical distribution of sediments overlying the Basement complex Rocks.
b. Exploration of fractured and/or weathered crystalline rocks within the basement rocks .
c- Search for water-bearing horizons, their depth, thickness and quality of their water content.
d- Location of suitable sites for drilling of boreholes for domestic uses.

Geophysical study results and recommendations One Horizontal Electrical Resistivity Profile (HEP) along selected favorable geological conditions (parallel to Wadi Medium) has been carried out for every selected area. Two Vertical Electrical Sounding (VES) have been conducted according to anomalies that result from the HEP measurements. The length of profiles was 300 m. The AB/2 and MN/2 were 75m and 25m respectively for HEP with station interval of 25m, whereas AB/2 was 200 m for VES (. VES 1).
The recommended VES point for drilling and its coordinates and expected depth is shown in table below.



(26.90, 26.54 , 26.35 , 23.37 , 25.55 , 25.49 , 29.22 , 25.20)

VES (1) Lat : 11.57695 Elevation =505 m

Long: 34.29280

AB/2	MN/2	Resistivity(0hm-m)
1.5	0.5	17.13
2.5		11.76
4		13.46
6		20.60
8		26.09
10		25.24
12		20.01
15		17.53
15	5	18.70
20		15.51
25		13.31
30		10.77
30	10	11.65
40		11.40
50		12.81
60		15.22
75		19.31
75	25	20.48
100		26.61
125		34.37
150		39.98
150	50	37.78
175		45.64
200		49.21



Descriptions of Layers:

From – To (meter)	Descriptions
0 - 15 m	Clay with Sand
15 – 25 m	Highly Weatherd Rock
25 – 35 m	Hard Rock
35 – 50 m	Fracture Rock
50 m >	Hard Rock

Recommendations:

After analyzing and interpreting the data, we concluded the following:

- ✓ It is recommended to drill the first point (VES1) according to the above mentioned coordinates to the depth ±50 meters.
- ✓ It is recommended to use air drilling method (Hammer) and Mud rotary machine.
- ✓ Based on the geological formations in the area and the ground water recharge as, as well previous studies, the water quantity will be required after pumping test.

PREPARED BY: HYDRO GEOPHYSICIST: SALAH ELDOMA ABD ALLA ABD ALRAHMAN

WES BLUE NILE MANGER: ABDELRAHIM MOHAMMED MAHMOUD